



PLAYER_3 PRO [4K] SDI



4K PLAYBACK IN A 1U PACKAGE

With a high performance NVIDIA GPU, 10GBE networking, SDI and HDMI, it delivers outstanding performance at a game-changing cost. Using industry standard codecs and control, Player_3_PRO [4K] delivers smooth playback when it really matters.

Designed from the ground up by experienced AV professionals Player_3_PRO [4K] from Hive is the next generation in media control.



AV DONE DIFFERENTLY



SPECIFICATIONS

Max media resolution	4320p 30 (8K)	Operating temperature	-20 to 35C°
Output resolution	4x 1080p 60	Cooling	Internal Fans (~45dB)
Max HEVC bit rate	500 @ 2160p60	Storage options	500GB, 1TB, 2TB, 4TB
Layers	2x 2160p 60 (4K)	Codecs	H.264, H.265, Avolites AiM
Connections	4x Mini SDI 3G 1x Mini SDI Ref Sync HDMI 2.0 (No SDI) USB 3.0 Gigabit Ethernet	Control	Comprehensive UPD command set, ArtNet
Power	54V 2.78A	Synchronisation	SMPTE MTC (USB), ArtNet timecode
Dimensions	W 430mm x D 250mm x H 44.5mm	Software	HIVE Web Serve UBUNTU 20.04
Weight	3235g	Render Engine	HIVE Render Engine
Rear mounting holes	1U Front mount	Processing	8 Core Arm Cortex-A78AE NVIDIA Ampere 1792 Core 32GB DDR5 256 Bit
		Accessories	

SOFTWARE

Hive's browser based software is powerful and easy to use and can be controlled from desktop or mobile devices. Create advanced playlists with follow-on commands and even synchronise multiple players to form extensive installations.

Product codes: Player_3_PRO-500GB, Player_3_PRO-1TB, Player_3_PRO-2TB, Player_3_PRO-4TB.

Video Storage Requirements (approx.)	250GB	500GB	1TB	2TB	4TB
ULTRA HD (2160p60) VIDEO - H.265 HEVC [240Mb/s] (in Mins)	125	250	500	1000	2000
ULTRA HD (2160p60) VIDEO - H.264 [240Mb/s] (in Mins)	125	250	500	1000	2000
ULTRA HD (2160p60) VIDEO - AVOLITES AIM (in Mins)	12	24	48	96	192



PRODUCT DIMENSIONS

